

PRODUCT DETAILS



DESCRIPTION: MACHINE-USE STRETCH FILM ID CODE: FESTMC001



ID CODE	DESCRIPTION	THICKNESS	ROLL HIGH	INTERNAL TUBE
FESTMC001	Low density linear polyethylene. Product for pallet winding. Raw material 100% Virgin LLDPE. PACKING: Reels placed in overlapping rows, protected with sheets of cardboard, and properly bandaged with extensible film. Automatic applications.	Thickness: 15, 17, 20, 23, 30, 35 my	500 mm	76 mm

DETAILS	U.M.	METHOD	TOLERANCE %	RESULT
Thickness	micron	UNI 8516	+ 10 - 0	23
Average weight of the coil	Kg		+ 3 - 3	16
Pallet weight	Kg		+ 2 - 2	736
Height	mm		+ 2 - 3	500
Internal diameter	mm		+ 1,5 - 1	76
External diameter	mm		+ 3 - 3	232
Longitudinal breaking load	Kg/mm2	ASTM D 882	> 0 =	3,25
Transversal breaking load	Kg/mm2	ASTM D 882	> 0 =	2
Longitudinal elongation to breaking	%	ASTM D 882	> 0 =	405
Transversal elongation to breaking	%	ASTM D 882	> 0 =	620
Pre-stretching	%	INT. IOSQ 004	> 0 =	100



Via Trento, 66/F - 20871 Vimercate (MB) - Italy
Tel: +039 6082860 - Fax: 039 6082890
Website: www.simisrl.it
TAC ID CODE and VAT: 07190670963
R.E.A. MB1874008 - Cap. Soc. € 100.000,00 i.v.

IBAN: IT 49 J 05034 32390 000000000876 // Swift/Bic: BAPPIT22
Banco Popolare Soc. Cooperativa - Agenzia Agrate Brianza (MB)